



EXCESS FLOW VALVE – 2000 SERIES **- 2100**

2100 Series Excess Flow Valves are designed to easily insert between ANSI class flanges for use in liquid or vapor service. These valves are lightweight, offer generous flow rates and are extremely durable. Available in carbon or stainless steel with other materials available upon request. The 2100 Series valve is equipped with a weep hole to allow for pressure equalization once the valve closes and is equipped with an auto reset feature. Closing flow rates are factory preset per customer requirements.

Model	Size	A Width	B Dia.	C Length	E Insert Dia.	CV Ranges*
2100-G	1.5"	1/2	2 7/8	2 5/8	1 1/2	9-17
2100-I	2"	1/2	3 5/8	3 11/32	1 29/32	18 - 22
2100-K	3"	1/2	5	3 23/32	2 7/8	22 - 45
2100-L	4"	5/8	6 3/16	4 11/16	3 3/4	65 – 80
2100-M	6"	3/4	8 1/2	7 7/32	5 11/16	80 – 182
2100-N	8"	3/4	10 5/8	8 3/16	7 1/2	182 – 343
2100-P	10"	7/8	12 3/4	11 5/16	9 5/8	343 – 600
2100-Q	12"	1.25	15	14 1/2	11 1/2	600 – 950
2100-R	14"	1.50	16 1/4	16 1/2	12 7/8	950-1225



Typical dimensions are listed. Data contained herein can be altered to accommodate design changes and changes to increase performance. Information on this page is the sole property of L6 Inc. d/b/a Total Valve Systems.

***Custom CVs upon request**

